

JouleBox 1000

Product Specifications
PS-JOULEBOX1000-01/02-180215

The **JouleBox** is an Energy Storage Solution based on Li-ion battery chemistry specifically designed for use with DC appliances. The **JouleBox** has a storage capacity of 1000kj and can supply up to 1.200.000kj (1200 MJ) over it's battery lifetime which depending on it's daily usage and rate of discharge will give a useful service life of 3 up to 10 years.

The **JouleBox** can be charged from LEC200 up to LEC1500 (or any type of 36 Cell 20Wp to 100Wp PV solar panel with Vmpp of 17.5V).

The **JouleBox** has 2 universal outputs to supply any DC appliances that can run from 12 to 16VDC source. Typical appliances that can be used with the **JouleBox** are Sundaya LCD TV of 18" up to 32" and Ceiling fans of 30 up to 70cm diameter.

The **JouleBox** also has 2 USB ports for charging USB devices like mobile phones and Tablets. Furthermore it is equipped with 2 docks with Bayonet fitting to recharge Sundaya JouleSticks that can be used in all Sundaya Portable products. The integrated electronics of the **JouleBox** take care of the health management of each cell's capacity to ensure a long life of the storage system. The electronics also protect against short circuit, overload, and overusage. A state of charge indicator provides information about the energy content in the **JouleBox**.



Energy

Energy Content	1.160 kj
Energy Available for usage	1.000 kj

Lifetime Energy Supply Capacity

@ 2 hour discharge rate	600.000 kj
@ 4 hour discharge rate	900.000 kj
@ 8 hour discharge rate	1.200.000 kj

Charging details

Max Charging Capacity (per hour)	400 kj/h
Max Charging Capacity (per second)	110 J/s (W)
Max Charge Current	8 A

Discharging details

Max Discharging Capacity (per hour)	500 kj/h
Max Discharging Capacity (per second)	140 J/s (W)
Max Discharging Current	10 A
Output Voltage Range	12-16 VDC

Input / Output Ports

Charging input port (5.5-2.0mm socket)	2 pcs
Load Output port (4.0-1.6mm socket)	2 pcs
USB output socket 5V, 2A	2 pcs
JouleStick Charging Dock 5V, 1A	2 pcs

Product Dimensions

Length	146 mm
Width	80 mm
Height	166 mm
Mass	2.100 gr

Protections

Protection on Inputs	Over Voltage Cut-off Over current Protection Reverse Polarity protection Reverse current protection Voltage surge protection
Protection on 12-16 V Outputs	Under Voltage Cut-off Over Load Protection Short Circuit Protection Reverse current protection
Protection on USB Outputs	Over Load Protection Short Circuit Protection

Others

Electronic Master On/Off Switch	Yes
State of Charge Indicator by green LED (activated upon switch press)	5 Blinks = 100% 4 Blinks = 80% 3 Blinks = 60% 2 Blinks = 40% 1 Blink = 20%
Low Voltage Cut-Off indicator	by Red LED

JouleBox 1000

Product Specifications
PS-JOULEBOX1000-02/02-180215

Mechanical Dimensions

